


408-2.5-75/408-6.5-150
Screwdrivers Straight

PRODUCT DETAILS

- For slotted straight head screws, electrician´s tip
- Sandblasted tip for better screw grip and full anti-rust guarantee
- For intensive use
- Two-component handle for comfortable grip and high torque transfer
- Non-rolling handle shape
- Integrated hanging hole
- High performance alloy steel blade, chrome plated and fully hardened
- Permanently marked blade with size and part number for easy identification
- Standards: ISO 2380, DIN 5264, UNE 16516



PRODUCT ATTRIBUTES

| Product | | | | | | | | |
|--------------------|--------|--------|--------|--------|-------|--------|--------|-------|
| 408-2.5-75 | 0.4 mm | 2.5 mm | 75 mm | 2.5 mm | 26 mm | 90 mm | 165 mm | 34 g |
| 408-3-75 | 0.5 mm | 3 mm | 75 mm | 3 mm | 26 mm | 90 mm | 165 mm | 35 g |
| 408-3-100 | 0.5 mm | 3 mm | 100 mm | 3 mm | 26 mm | 90 mm | 190 mm | 40 g |
| 408-3-200 | 0.5 mm | 3 mm | 200 mm | 3 mm | 26 mm | 90 mm | 290 mm | 45 g |
| 408-3.5-100 | 0.6 mm | 3.5 mm | 100 mm | 3.5 mm | 26 mm | 90 mm | 190 mm | 40 g |
| 408-4-100 | 0.8 mm | 4 mm | 100 mm | 4 mm | 26 mm | 90 mm | 190 mm | 45 g |
| 408-4-125 | 0.8 mm | 4 mm | 125 mm | 4 mm | 26 mm | 90 mm | 215 mm | 45 g |
| 408-4-250 | 0.8 mm | 4 mm | 250 mm | 4 mm | 26 mm | 90 mm | 340 mm | 60 g |
| 408-5.5-125 | 1 mm | 5.5 mm | 125 mm | 5.5 mm | 30 mm | 100 mm | 225 mm | 65 g |
| 408-5.5-150 | 1 mm | 5.5 mm | 150 mm | 5.5 mm | 30 mm | 100 mm | 250 mm | 90 g |
| 408-5.5-300 | 1 mm | 5.5 mm | 300 mm | 5.5 mm | 30 mm | 100 mm | 400 mm | 106 g |
| 408-6.5-150 | 1.2 mm | 6.5 mm | 150 mm | 6.5 mm | 34 mm | 110 mm | 260 mm | 110 g |